

80MM RECEIPT/TICKET PRINTER

VKP80II SX

- 200dpi best printing quality
- Paper width from 60 to 82.5mm (adjustable paper-in for different paper width)
- Speed > of 220mm/sec
- Automatic ticket ejecting & retracting back (speed > of 1000 mm/s)
- High power motor feeder for huge paper roll (up to 300 mm Ø)
- Multiposition paper roll
- RS232+USB / RS232+USB+Ethernet interface
- 1D/ 2D barcodes printing capability (QRCODE, PDF417 and DATAMATRIX for ETH version)
- International fonts on board: any language available
- 4MB internal flash memory for logos and fonts
- Highly reliable cutter: > of 1.500.000 cuts
- Sensors: paper end, black mark, ticket presence, printing unit opening and paper low on roll holder
- Self-balancing paper roll support
- Illuminated paper bezel
- Patented anti-jamming system
- Outdoor applications: -20/+ 70°C working temperature

CEPRINTERSET SOFTWARE: to update logos, to edit fonts, to set the working parameters and update printer's firmware. Create a file including the different SW customisations and send it to the printer through the interface for an easy and quick setting.

SOFTWARE FEATURES

- Total remote management by internal Web Server
- Automatic email sending for service purpose
- Status Monitor DLL
- Full Windows Status Monitor Driver
- Self-installing Driver for WinXP/Vista/7/8/8.1/10
- Linux Driver (C.U.P.S.) 32/64 bit compatible
- WOSA XFS Driver
- OPOS & JavaPOS Driver

SHUTTER FOR OUT-DOR:

- It allows to reduce the onsite technical assistance costs, because it significantly increases the life of the internal components
- Prevents the accidental introduction of objects in the printer bezel
- No need any firmware update
- It installs easily, even in the field (retrofit)

OPERATING CONDITIONS:

- Min paper weight 60gr/mq with 85% not condensed relative humidity
- Operating temperature -20 /+70°C



SDK and APP available

